

Battery-Operated Smart Ram 640T

Install Pop-A-Plug® Tube Plugs with Ease!

Quickly perform heat exchanger tube repairs without significant setup or breakdown time. Self-contained battery-operated hydraulic unit provides reliable installation of heat exchanger tube plugs. Long-lasting 18v/3.0Ah Lithium-ion battery allows for cordless operation in remote and close quarters environments without the need for electric or plant air connection.

Size Range Capability

- **Pop-A-Plug® CPI/Perma Plugs:** V471 thru V1212
 - Tube ID: 0.472" to 1.336" (11.99 mm - 33.93 mm)
- **Pop-A-Plug® P2 Plugs:** P2400 thru P21160
 - Tube ID: 0.400" to 1.180" (10.19 mm - 29.99 mm)

Weight

- 5lbs (2.3kg)

Features

- Ideal for remote or confined spaces
- Eliminates tripping hazards
- Self-contained unit - no shop air or electric required
- Long-lasting 3.0Ah Li-Ion Battery
- Install up to 500 tube plugs on fully charged battery
- Install with BAW or Pull-to-Pressure methods
- Info display with multi-user preset capabilities

For additional installation, sizing and Pull Rod Assembly information, please reference:

- [DC1230 - Smart Ram 640T Operating Procedures](#)

